## Firemark Limited

## **COSHH ASSESSMENT**

Product Name	(s): AdBl	AdBlue							17
Description of Substance:	Diese	el Additive, con	tains Urea			Asses	sed By:	J Vic	kery
Workplace Exposure Limi	ts: LD50	14,300 – 15,0	00 mg / kg ora	al		Date:		25/0	1/2022
						Hazaro Staten	-		
Task/Activity:	Diese	Diesel additive						P101	P102 P501
Suppliers Name & Holt Lloyd International Limited, Manchester M32					Telephone/ Fax No's:		0161	866 4800	
Address:							ed:	Yes	
	SUBSTANCE PROPERTIES								
							×		F
Flammable/ Highly Flammable	Oxidiser	Explosive	Harmful	Toxic/ Very Toxic	Irri	Irritant Dangerou Environn			Corrosive
No	No	No	No	No	Ν	lo	No		No

ROUTE OF EXPOSURE					PERSONS AT RISK						
Skin	X	Eyes	X	Inhalation	х	Users of the product	х	Members of Public	х	Visitors	x
Ingestion		Cuts/ Abrasions		Injection		Other Workers	х	Young Persons	х		

PPE REQUIREMENTS								
					B	Other:	Other:	
Yes	No	No	No	Yes	No	No	No	

ADDITIONAL CONTROL MEASURES					
General Precautions	Control Measures				
Contact with the liquid may cause irritation so wear gloves if required when filling van. Wear gloves if any risk of splashes	None				

## Firemark Limited

First Aid/Hygiene Arrangements	Fire Precautions
Inhalation: remove patient to fresh air and seek medical attention.	None as not flammable.
Ingestion: Do not induce vomiting. Drink plenty of water. Seek medical attention if discomfort continues. Skin/eye: flush with water for 15 minutes. Seek medical attention if irritation / discomfort continues	Will produce hazardous products, oxides of carbon and nitrogen from decomposition

LEV Requirements	Monitoring Requirements
None	None

Transport Arrangements	Storage Requirements
Non hazardous	Keep away from heat.

Spillage Procedures	Disposal Requirements
Not hazardous unless as only in 10 L maximum drums	In accordance with local Waste Disposal Authority

## Comments

Diesel additive used by all diesel vehicle drivers