

Foam Extinguishers



Foam spray extinguishers, (AFFF- Aqueous Film Forming Foam), are ideal for multi-risk situations where both Class A combustible materials and Class B flammable liquid risks are likely to be found, or where Class B represents a direct hazard.

Foam spray extinguishers are especially suitable for Class B fires involving flammable liquids such as oils, spirits, fats and certain plastics. The blanketing effect of foam spray gives rapid knock down which smothers the flame and thus prevents re-ignition of flammable vapours by sealing the surface of the solution.



MODEL	F9/1	F6/1	F6/2	F2/1
Type	Foam	Foam	Foam	Foam
Capacity (litre)	9	6	6	2
Full Weight (kg)	13.7	9.5	9.5	3.2
Cylinder Weight (kg)	4.3	2.9	2.9	1.2
Cylinder Height (mm)	474	429	429	395
Cylinder Diameter (mm)	185	160	160	108
Minimum Discharge (s)	68	44	44	6
Temperature Range (°c)	+5 to 60	+5 to 60	+5 to 60	+5 to 60
Working Pressure at 20°C	12 bar	12 bar	12 bar	12 bar
Test Pressure	30 bar	30 bar	30 bar	28 bar
Fire Rating	27A:233B	21A:183B	34A:183B	8A:55B
Approved to BS EN3	Yes	Yes	Yes	Yes
Marine Approved	Yes	Yes	Yes	No

Ref: FoamTDS | 01/2020 | Rev 1